FLIGHT SUMMARY REPORT

Flight Number: 96-135

Calendar/Julian Date: 15 June 1996 • 167

Sensor Package: Dual Wild-Heerbrugg RC-10

Airborne Visible and Infrared Imaging

Spectrometer (AVIRIS)

Area(s) Covered: Palmdale/Ivanpah Playa, CA

Investigator(s): Green and Farr, JPL Aircraft #: 708

SENSOR DATA

Accession #:	05091	05092	
Sensor ID #:	026	076	099
Sensor Type:	RC-10	RC-10	AVIRIS
Focal Length:	12" 304.97 mm	12" 304.89 mm	
Film Type:	Aerochrome IR SO-060	Aerochrome IR SO-060	
Filtration:	Wratten 12	Wratten 12	
Spectral Band:	510-900 nm	510-900 nm	
f Stop:	11	8	
Shutter Speed:	1/275	1/550	
# of Frames:	70	66	
% Overlap:	60	60	
Quality:	Excellent	Excellent	

Remarks: Camera clock offset

Camera clock offset
44 seconds from
navigation data

Camera clock offset
1.35 minutes from
navigation data

Airborne Science and Applications Program

The Airborne Science and Applications Program (ASAP) is supported by three ER-2 high altitude Earth Resources Survey aircraft. These aircraft are operated by the High Altitude Missions Branch at NASA-Ames Research Center, Moffett Field, California. The ER-2s are used as readily deployable high altitude sensor platforms to collect remote sensing and in situ data on earth resources, celestial phenomena, atmospheric dynamics, and oceanic processes. Additionally, these aircraft are used for electronic sensor research and development and satellite investigative support.

The ER-2s are flown from various deployment sites in support of scientific research sponsored by NASA and other federal, state, university, and industry investigators. Data are collected from deployment sites in Kansas, Texas, Virginia, Florida, and Alaska. Cooperative international scientific projects have deployed the aircraft to sites in Great Britain, Australia, Chile, and Norway.

Photographic and digital imaging sensors are flown aboard the ER-2s in support of research objectives defined by the sponsoring investigators. High resolution mapping cameras and digital multispectral imaging sensors are utilized in a variety of configurations in the ER-2s' four pressurized experiment compartments. The following provides a description of the digital multispectral sensor(s) and camera(s) used for data collection during this flight.

Airborne Visible and Infrared Imaging Spectrometer

The Airborne Visible and Infrared Imaging Spectrometer (AVIRIS) is the second in the series of imaging spectrometer instruments developed at the Jet Propulsion Laboratory (JPL) for earth remote sensing. This instrument uses scanning optics and four spectrometers to image a 614 pixel swath simultaneously in 224 contiguous spectral bands (0.4-2.4 mm).

AVIRIS parameters are as follows:

IFOV: 1 mrad

Ground Resolution: 66 feet (20 meters) at 65,000 feet

Total Scan Angle: 30°

Swath Width: 5.7 nmi (10.6 km) at 65,000 feet

Spectral Coverage: 0.41-2.45 mm

Pixels/Scan Line: 614
Number of Spectral Bands: 224
Digitization: 10-bits
Data Rate: 17 MBPS

	Wavelength	Number of	Sampling
Spectrometer	Range	Bands	Interval
1	0.41 - 0.70 mm	31	9.4 nm
2	0.68 - 1.27 mm	63	9.4 nm
3	1.25 - 1.86 mm	63	9.7 nm
4	1.84 - 2.45 mm	63	9.7 nm

All AVIRIS data is decommutated and archived at JPL and not currently available for public distribution. For further information contact Rob Green at Jet Propulsion Laboratory, 4800 Oak Grove Drive, Mail Stop 183-501, Pasadena, California 91109-8099.

Camera Systems

Various camera systems and films are used for photographic data collection. Film types include high definition color infrared, natural color, and black and white emulsions. Available photographic systems are as follows:

- Wild-Heerbrugg RC-10 metric mapping camera
 - 9 x 9 inch film format
 - 6 inch focal length lens provides area coverage of 16 x 16 nautical miles from 65.000 feet
 - 12 inch focal length lens provides area coverage of 8 x 8 nautical miles from 65,000 feet
- Hycon HR-732 large scale mapping camera
 - 9 x 18 inch film format
 - 24 inch focal length lens provides area coverage of 4 x 8 nautical miles from 65,000 feet
- IRIS II Panoramic camera
 - 4.5 x 34.7 inch film format
 - 24 inch focal length lens
 - 90 degree field of view provides area coverage of 2 x 21.4 nautical miles from 65,000 feet

The U.S. Geological Survey's EROS Data Center at Sioux Falls, South Dakota serves as the archive and product distribution facility for NASA-Ames aircraft acquired photographic and digital imagery. For information regarding photography and digital data (including areas of coverage, products, and product costs) contact EROS Data Center, Customer Services, Sioux Falls, South Dakota 57198 (Telephone: 605-594-6151).

Additional information regarding ER-2 acquired photographic and digital data is available through the Aircraft Data Facility at Ames Research Center. For specific information regarding flight documentation, sensor parameters, and areas of coverage contact the Aircraft Data Facility, NASA-Ames Research Center, Mail Stop 240-6, Moffett Field, California 94035-1000 (Telephone: 415-604-6252).

CAMERA FLIGHT LINE DATA FLIGHT NO. 96-135

Accession # 05091

Sensor # 026

Check	Frame	Time (GMT-hr, min, sec)		Altitude, MSL	
Points	Numbers	START	END	feet/meters	Cloud Cover/Remarks
A - B	6686-6706	18:27:47	18:37:10	65276/19896	Clear
B - A	6707-6728	18:43:42	18:53:32	65382/19928	Clear
C - D	6729-6748	19:08:07	19:16:59	64940/19794	Clear
D - E	6749-6755	19:23:12	19:25:59	64757/19738	Clear

CAMERA FLIGHT LINE DATA FLIGHT NO. 96-135

Accession # 05092

Sensor # 076

Check	Frame	Time (GMT-hr, min, sec) Altitude, MSL		Altitude, MSL	
Points	Numbers	START	END	feet/meters	Cloud Cover/Remarks
F - C	1548-1553	19:29:31	19:31:56	65183/19868	Clear
C - D	1554-1574	19:39:20	19:48:38	65319/19909	Clear
D - C	1575-1593	19:55:05	20:03:24	64605/19692	Clear
C - D	1594-1613	20:10:55	20:20:07	64790/19748	Clear



